


## Front Seat Net Pet Barrier<sup>™</sup> Care & Use Guide

Thank you for purchasing the Solvit Products Front Seat Net Pet Barrier<sup>TM</sup>. This barrier is designed for installation behind the front seat in all vehicles with headrests.

**WARNING**: The mesh barrier is attached to a coiled metal frame which might "pop open" when removed from the pouch - remove carefully in an open area. The pouch should contain the mesh barrier, support rod and 2 cinch straps.

Installation: To ease installation, consider raising each front seat head rest to clearly expose the metal headrest posts (they can be returned to their normal position after installation). Allow the mesh barrier to "pop open" to its natural, square shape. Assemble the support rod with the coupler between the two straight sections. Insert one end of the support rod into the small "pocket" at the bottom edge of the barrier. While bending the support rod slightly, insert the other end into the pocket at the top edge of the barrier.



Attach the swivel hooks from each cinch strap onto one of the fabric loops sewn into the sides of the barrier. There are two loops on each side – most vehicles will fit best using the lower loops. With the support rod on the "front seat" side of the barrier, thread the cinch straps around the outer headrest posts and loop back through the cinch rings. Tighten each cinch strap so the barrier is centered between the two seats. If the barrier rides too high, consider changing the swivel hooks to the upper fabric loops.

Install the Sta-Put<sup>TM</sup> tube in the front passenger seat by pushing the plastic tube into the space between the seat back and seat bottom. Tighten the Sta-Put<sup>TM</sup> strap so the bottom edge of the barrier rests firmly against the back of the seats and/or console (it might be necessary to hold the Sta-Put<sup>TM</sup> tube in place when adjusting the strap). Tuck any extra strap material between the seat cushions. The Sta-Put<sup>TM</sup> tube can be removed with a strong tug, but should stay in place under normal conditions.

To "fold down" the barrier for storage, remove the support rod, then while holding

the left and right sides, twist hands in opposite directions while bringing hands together. The wire frame should form three concentric circles. Align the circles then place barrier in the storage pouch. Handle carefully as the barrier can "pop open" if not held in this stowed position.

Cleaning & Safety: Wipe with damp cloth or sponge and mild cleaner. No machine wash. Never leave pets in vehicle unattended.

Warranty: The Front Seat Net Pet Barrier is warranted to be free from defects in materials or workmanship for a period of one (1) year from the date of purchase. A copy of the original sales receipt is required for warranty issues.

seat back

Solvit Products is dedicated to offering innovative solutions to improve pets' quality of life. Please feel free to contact us with and questions, comments, or warranty issues. Thank you for your purchase!